Technical Data Sheet

Commodity:



(626)363-8855 Fax: (626)363-8856 951 Lawson St., City of Industry, CA 91748, www.colorwen.com Email: info@colorwen.com

Orange 202P

PO 16	CAS No.:6505-28-8	
>1.30	(Water=1)	
36 ± 5.0	g Oil / 100g Pigment	
<1.5%		
100±5%		
$\Delta E < I$		
6-8		
5		
4		
	>1.30 36±5.0 <1.5% 100±5% $\triangle E < 1$ 6-8	

Resistance to Solvents (1-5 Scale; 5 denotes the best)				
Water	5	Toluene	5	
Ethyl Alcohol	5	Ethyl Acetate	4	
Methyl Ethyl Ketone	5			

Resistance to Acid	and Alkali (1-5 scale; 5 denotes the best)	
2% HCL	5	2% NaOH	5

Recommended for

Offset Ink, Coating, Plastics, Rubber, Textile

Light fastness: 1-8 scale; 8 the best Others: 1-5 scale; 5 the best

Any information and data stated herein is only offered as suggestion for an investigation for use based on our test. They are no-binding and can not be taken as a guarantee. No warranty, either expressed or implied, is made or intended. It's the responsibility of the buyer to test and determine the safety and suitability.