Technical Data Sheet



(626)363-8855 Fax: (626)363-8856 951 Lawson St., City of Industry, CA 91748, www.colorwen.com Email: info@colorwen.com

Commodity:	Red 1254	
C. I. Name:	PR:254	CAS No.:122390-98-1

Specific Gravity	>1.40	(Water=1)
Oil Absorption	47 ± 5.0	g Oil / 100g Pigment
Moisture	<1.5%	
Color Strength	$100{\pm}5\%$	
Color Shade Variance	$\Delta E < 1$	

Fastness Properties		
Heat Resistance	5	270°C x 5min.
Light Fastness	7-8	
Migration	5	

Resistance to Solvents (1-5 Scale; 5 denotes the best)				
Water	4-5	Toluene	4-5	
Ethyl Alcohol	4-5	Ethyl Acetate	4-5	
Methyl Ethyl Ketone	4-5			

Wiethyr Ethyr Rete	110		
Resistance to Ad	cid and Alkali (1-5 scale	; 5 denotes the best)	
2% HCL	4-5	2% NaOH	4-5

Recommended for

Paints and Coatings, Textile, Offset, Plastics

Light fastness: 1-8 scale; 8 the best Others: 1-5 scale; 5 the best

Any information and data stated herein is only offered as suggestion for an investigation for use based on our test. They are no-binding and can not be taken as a guarantee. No warranty, either expressed or implied, is made or intended. It's the responsibility of the buyer to test and determine the safety and suitability.