## Technical Data Sheet



(626)363-8855 Fax: (626)363-8856 951 Lawson St., City of Industry, CA 91748, www.colorwen.com Email: info@colorwen.com

| Commodity:  | Red 107K |                   |
|-------------|----------|-------------------|
| C. I. Name: | PR 57:1  | CAS No.:5281-04-9 |
|             |          |                   |

| General Properties   |                |                      |
|----------------------|----------------|----------------------|
| Specific Gravity     | >1.40          | (Water=1)            |
| Oil Absorption       | 42±5.0         | g Oil / 100g Pigment |
| Moisture             | <1.5%          |                      |
| Color Strength       | $100{\pm}5\%$  |                      |
| Color Shade Variance | $\Delta E < 1$ |                      |
|                      |                |                      |
| PH                   | 7.0-8.0        |                      |

| Fastness Properties |   |       |  |
|---------------------|---|-------|--|
| Heat Resistance     | 5 | 180°C |  |
| Light Fastness      | 6 |       |  |
| Migration           | 4 |       |  |

| Resistance to Solvents (1-5 Scale; 5 denotes the best) |     |               |   |  |
|--|-----|---------------|---|--|
| Water  | 3-4 | Toluene       | 3 |  |
| Ethyl Alcohol  | 4   | Ethyl Acetate | 3 |  |
| Methyl Ethyl Ketone                                    | 3   |               |   |  |

| Resistance to Acid | and Alkali (1-5 s | cale; 5 denotes the best) |   |
|--------------------|-------------------|---------------------------|---|
| 2% HCL             | 4                 | 2% NaOH                   | 3 |

## Recommended for

Offset, Coating, Plastics, Textile

Light fastness: 1-8 scale; 8 the best Others: 1-5 scale; 5 the best

Any information and data stated herein is only offered as suggestion for an investigation for use based on our test. They are no-binding and can not be taken as a guarantee. No warranty, either expressed or implied, is made or intended. It's the responsibility of the buyer to test and determine the safety and suitability.